

**Heated Terminal Holder**

1650 Dove Court, Marietta, Georgia 30064 USA Phone: 770.499.9420 Toll Free: 888.499.9420 [www.jlcsolutions.com](http://www.jlcsolutions.com)



The **JLC Solutions** heated terminal holder eliminates the “Fogging” and “Freezing” on the laser scanner lens and on the terminal’s display screen caused by temperature and humidity changes. This is accomplished by placing two thermostatically controlled heating pads designed to put the right amount of heat at both key points. This thermostatically controlled heated holder is a reliable solution on the issue of condensation with handheld terminals.

---

The heated terminal holder serves as a rugged and secure storage device that protects the portable terminal from damage and the lens and display screen from scratches.

---

In any type of application where the lens or display screen is likely to fog or freeze, the terminal will be rendered virtually useless without protection. It is in exactly this type of environment, with the terminal moving back and forth from -22F to +110F, that the **JLC Solutions** heated terminal holder was developed and tested.

---

The terminal heated will ensure “good reads” in the harsh environment where rapid or extreme temperature changes occur such as traveling from a refrigerated or frozen storage area to a loading dock, from an air-conditioned warehouse to outdoors, or any place where condensation is likely to occur on the scanner lens or the display.

---

The **JLC Solutions** heater portable terminal holder’s ABS housing with the fully adjustable anodized aluminum mounting bracket will withstand years of heavy industrial use. The heater is available in 12, 24, 36/48 volt models.

**Heated Terminal Holder**
**Product Specifications**

Part Number	Description
127-12	Heated Terminal Holder, 12 Volt
127-24	Heated Terminal Holder, 24 Volt
127-3648	Heated Terminal Holder, 36-48 Volt

Mechanical	
<b>Dimensions</b>	11 1/4 x 5 3/4 x 5 1/2" 28.2 x 14.5 x 14 cm
<b>Mounting</b>	Includes adjustable mounting bracket

Environmental	
<b>Dust and Water</b>	
Dust	Dust will not interfere with the product.
Water	Water splashed against the enclosure from any direction shall have no harmful effect.
<b>Temperature Rating</b>	Storage    -40F - +160F    -38C - +71C Operating   -25F - +120F    -31C - +49C
<b>Fixed Mount Shock Rating</b>	10 G

Specifications are subject to change without notice

**Heated Terminal Holder**
**Product Specifications**

Electrical																															
<b>RoHS Compliant</b>	<b>REACH Compliant</b>																														
<b>Operating Voltage</b>	12 - 48 Volt DC																														
<b>Polarity</b>	Independent, protected from reverse installations Overtemp protection fused at 250F (121C)																														
<b>Indicators</b>	Power On      Green LED Heater On      Red LED																														
<b>Operating Current</b>	With Heater On: <table border="1"> <thead> <tr> <th></th> <th><u>12V</u></th> <th><u>24V</u></th> <th><u>36V</u></th> <th><u>48V</u></th> </tr> </thead> <tbody> <tr> <td>Amps</td> <td>3.2</td> <td>3.2</td> <td>3.2</td> <td>3.2</td> </tr> <tr> <td>Temp On</td> <td>140F 60C</td> <td>140F 60C</td> <td>140F 60C</td> <td>140F 60C</td> </tr> </tbody> </table> With Heater Off: <table border="1"> <thead> <tr> <th></th> <th><u>12V</u></th> <th><u>24V</u></th> <th><u>36V</u></th> <th><u>48V</u></th> </tr> </thead> <tbody> <tr> <td>Amps</td> <td>.1</td> <td>.1</td> <td>.1</td> <td>.1</td> </tr> <tr> <td>Temps Off</td> <td>165F 74C</td> <td>165F 74C</td> <td>165F 74C</td> <td>165F 74C</td> </tr> </tbody> </table>		<u>12V</u>	<u>24V</u>	<u>36V</u>	<u>48V</u>	Amps	3.2	3.2	3.2	3.2	Temp On	140F 60C	140F 60C	140F 60C	140F 60C		<u>12V</u>	<u>24V</u>	<u>36V</u>	<u>48V</u>	Amps	.1	.1	.1	.1	Temps Off	165F 74C	165F 74C	165F 74C	165F 74C
	<u>12V</u>	<u>24V</u>	<u>36V</u>	<u>48V</u>																											
Amps	3.2	3.2	3.2	3.2																											
Temp On	140F 60C	140F 60C	140F 60C	140F 60C																											
	<u>12V</u>	<u>24V</u>	<u>36V</u>	<u>48V</u>																											
Amps	.1	.1	.1	.1																											
Temps Off	165F 74C	165F 74C	165F 74C	165F 74C																											

Warranty	
<b>Standard</b>	The factory warranty is one (1) year limited parts and labor.

Specifications are subject to change without notice