

**523  
Heated Laser Scanner Holder**

1650 Dove Court, Marietta, Georgia 30064 USA Phone: 770.499.9420 Toll Free: 888.499.9420 [www.jlcsolutions.com](http://www.jlcsolutions.com)



**523 Scanner Heater** eliminates the “Fogging” and “Condensation” on the laser scanner lens caused by temperature and humidity changes. The JLC heated scanner holder is used extensively throughout the rugged refrigerated warehouse and food production industries. The thermostatically controlled heated holder has proven itself as a reliable solution to the issues of hand held laser scanning. Scratched lenses, damaged scanners and fogged lenses are all expensive problems that are minimized if not completely eliminated with the **523** heated laser scanner holders.

Our **523 Scanner Heater** is a newly designed smaller heater made to extend the battery life of a scanner. This smaller unit takes up less real-estate on the lift trucks allowing more space to operate. The **523** also has a smaller footprint in order to make mounting easier and minimizes the amount of space used on a fork lift.

In any type of application where the lens is likely to fog, the laser scanner will be rendered virtually useless without protection. It is in exactly this type of environment, with the scanner gun moving back and forth from  $-25^{\circ}\text{F}$  to  $+110^{\circ}\text{F}$ , that the **523** was developed and tested.

Our **523** will insure “good reads” in the harsh environments where rapid or extreme temperature changes occur such as traveling from a refrigerated or frozen storage area to a loading dock, from an air-conditioned warehouse to outdoors, or any place where condensation is likely to occur on the scanner lens.

The **523's** ABS housing with the fully adjustable anodized aluminum mounting bracket will withstand years of heavy industrial use. The **523** heater is available in 12, 24, 36/48 volt models and is now custom-fitted for the Intermec SR61 laser scanners. Installation is quick and easy.

**523 Scanner Heater** will protect your investment and save expensive repairs by preventing lens fogging, condensation inside the scanner while securing the scanner itself from damage.

**Product Specifications**
**523**
**Heated Laser Scanner Holder**

Part Number	Description	Compatibility
523-12-N3	Heated Scanner Holder, 12 Volt	Intermec SR61 Series
523-24-N3	Heated Scanner Holder, 24 Volt	Intermec SR61 Series
523-3648-N3	Heated Scanner Holder, 36-48 Volt	Intermec SR61 Series

Mechanical	
<b>Dimensions</b>	7 1/2 x 4 3/4 x 3 1/2" 19.1 x 12.1 x 8.9 cm
<b>Mounting</b>	Includes adjustable mounting bracket

Environmental	
<b>Dust and Water</b>	
Dust	Dust will not interfere with the product.
Water	Water splashed against the enclosure from any direction shall have no harmful effect.
<b>Temperature Rating</b>	Storage    -40F - +160F    -38C - +71C Operating    -25F - +120F    -31C - +49C
<b>Fixed Mount Shock Rating</b>	10 G

Specifications are subject to change without notice

**523**

**Heated Laser Scanner Holder**

**Product Specifications**

<b>Electrical</b>																																	
<b>RoHS Compliant</b>	<b>REACH Compliant</b>																																
<b>Operating Voltage</b>	12 - 48 Volt DC																																
<b>Polarity</b>	Independent, protected from reverse installations Overtemp protection fused at 250F (121C)																																
<b>Indicators</b>	Power On      Green LED Heater On      Red LED																																
<b>Operating Current</b>	With Heater On: <table border="0" style="margin-left: 20px;"> <tr> <td></td> <td><u>24V</u></td> <td><u>36V</u></td> <td><u>48V</u></td> </tr> <tr> <td>Amps</td> <td>1.6</td> <td>.76</td> <td>1.02</td> </tr> <tr> <td>Temp On</td> <td>140F</td> <td>140F</td> <td>140F</td> </tr> <tr> <td></td> <td>60C</td> <td>60C</td> <td>60C</td> </tr> </table> With Heater Off: <table border="0" style="margin-left: 20px;"> <tr> <td></td> <td><u>24V</u></td> <td><u>36V</u></td> <td><u>48V</u></td> </tr> <tr> <td>Amps</td> <td>.1</td> <td>.1</td> <td>.1</td> </tr> <tr> <td>Temps Off</td> <td>165F</td> <td>165F</td> <td>165F</td> </tr> <tr> <td></td> <td>74C</td> <td>74C</td> <td>74C</td> </tr> </table>		<u>24V</u>	<u>36V</u>	<u>48V</u>	Amps	1.6	.76	1.02	Temp On	140F	140F	140F		60C	60C	60C		<u>24V</u>	<u>36V</u>	<u>48V</u>	Amps	.1	.1	.1	Temps Off	165F	165F	165F		74C	74C	74C
	<u>24V</u>	<u>36V</u>	<u>48V</u>																														
Amps	1.6	.76	1.02																														
Temp On	140F	140F	140F																														
	60C	60C	60C																														
	<u>24V</u>	<u>36V</u>	<u>48V</u>																														
Amps	.1	.1	.1																														
Temps Off	165F	165F	165F																														
	74C	74C	74C																														

<b>Warranty</b>	
<b>Standard</b>	The factory warranty is one (1) year limited parts and labor.

Specifications are subject to change without