



Installation Manual

Cablesaver





Congratulations on your purchase of a quality *JLC Solutions* product. All of us at *JLC Solutions* take pride in the design and assembly of each of our products and we believe that your experience will be positive.

Ordering, Information and Support

Phone: 770.499.9420

Web Site: www.jlcsolutions.com

E-mail: orders@jlcsolutions.com
sales@jlcsolutions.com
info@jlcsolutions.com
support@jlcsolutions.com

Warranty

JLC Solutions stands behind its products with a one year limited warranty for defects in workmanship and materials, and will handle any issues that may arise in a professional and timely manner.

PLEASE READ AND UNDERSTAND ALL DOCUMENTATION, INSTRUCTIONS, WARRANTY AND SAFETY INFORMATION PRIOR TO PROCEEDING WITH YOUR INSTALLATION.

VERIFY THAT THE PARTS RECEIVED ARE COMPLETE AS DETAILED WITHIN THE PARTS LIST FOUND IN THIS MANUAL.

If you have any concerns or questions relative to the installation of your *JLC Solutions* product, please contact *JLC Solutions* for further assistance or clarification.

Contents

<i>Cablesaver</i> Cable Management Installation	pages 3 – 6
Mounting Options	page 7
Standards Committees and Organizations and Parts List	page 8

Installation Detail

Scanner Installation

1. Locate 1 cable tie on the *Cablesaver* and 4 cable ties in the package (3 large, 1 small) as seen in Figure 1.

Figure 1



2. Secure 1 large cable tie to the scanner cable at the end near laser scanner. (Figures 2 & 3).

Figure 2



Figure 3



3. Secure the second large cable tie to the approximate mid-point of scanner cable. (Figure 4)

Figure 4



Installation Detail

Scanner Installation (cont.)

4. Determine where the **Cablesaver** is going to be placed in relation to the terminal. After leaving enough of the scanner's cable to go between the terminal and the **Cablesaver** secure the third large cable tie to scanner's cable as shown in Figure 5.

Figure 5



5. Place a supplied small cable tie through slot in the scanner handle as shown in figure 6.

Figure 6



6. Draw the small cable tie around the base of the scanner as shown.

Figure 7



Installation Detail

Scanner Installation (cont.)

7. Tighten the cable tie as shown in figure 8. This method will allow for the screws at the bottom of the scanner to be removed and the scanner cable to inserted or removed as necessary without affecting the *JLC Solutions* retractor cable tie.



Figure 8

8. Pull the retractor cable through the eyes on the cable ties. (Figure 9)



Figure 9

9. Place the supplied ring on the bottom of the laser scanner. Secure the *Cablesaver* cable to the ring on the scanner's cable tie. (Figure 10)



Figure 10

10. Secure the remaining cable tie (permanently fastened to *Cablesaver*) around the portion of the scanner cable that goes to the terminal. This will prevent strain on the end of the scanner cable that connects to the terminal during use.

Figure 11



Installation Detail

Mounting Bracket

The mounting bracket allows the *Cablesaver* to be raised off a desk or deck surface or used in an overhead position. The “L” bracket can also be used as a right or left side mount and can be welded.



Standards Committees and Organizations

You must follow all standards, rules, regulations and codes that may apply to your particular installation. These standards, rules, regulations and codes vary considerably across the various regions of the world and within the various industries. *JLC Solutions* cannot provide definitive information in regards to these worldwide safety and installation issues. In order to provide some guidance in regards to these and other installation and safety issues, please contact the appropriate organization, association, government agency or committee that has jurisdiction over your individual installation and application.

RoHS All *JLC Solutions* products are RoHS compliant.

REACH All *JLC Solutions* products are REACH compliant.

Parts List

Cablesaver



Scanner Retractor Connection Ring



3 Large, 1 Small Cable Ties

